

data driver for sending display data to said liquid crystal display device, said data driver power circuit comprising:

an input power supply serving as a universal power supply therefore;

an amplifying element having an input terminal connected to said input power supply, and having a control terminal, and an output terminal from which the data driver power voltage is outputted;

an electric current limiting resistor having a first terminal connected to said input power supply, and having a second terminal connected to said control terminal of said amplifying element;

a diode group including a plurality of series-connected diodes wherein a cathode terminal of a first diode is connected to ground and an anode terminal of a last diode is connected to said control terminal of said amplifying element, and each other diode in the series having a cathode terminal connected to an anode terminal of the preceding diode; and

a capacitor having a first terminal connected to said output terminal of said amplifying element, and a second terminal connected to ground.

18. (New) The power supply circuit according to claim 1, wherein the data driver power circuit performs, at the same time, a voltage regulation function, a temperature compensation function, and a power supply function for the liquid crystal display.

IN THE ABSTRACT

Please amend the abstract as indicated in the attachment submitted herewith.

a³
concl.

a 4 Sub
D

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com